

NACHI


NACHI

Spherical Roller Bearings
EX-V Series
For Vibrating Applications



EX-V series

NACHI is proud to introduce our **NEW VIBRATING SCREEN BEARING** for applications with high impact or heavy vibrations. NACHI integrated a hardened steel cage into the standard EX High Capacity Bearings.



EX-V is 10 times more impact-resistant than standard cages.

Test Condition

Vibrating cycles : 119 cpm
 Vibrating acceleration : 200 G
 Temperature : ambient

EX-V Series Features

Increased Strength

The new EX-V cage has increased tensile strength, is more fatigue resistant and more resistant to wear.

High Load Capacity

NACHI's EX-V spherical roller bearing design maintains high load capacities by utilizing the longest length & largest diameter rollers in the market.

Lower Operating Temperature

The floating guide ring and new EX-V cage design generates less heat & promotes lower operating temperatures.

NACHI P/N	Boundary dimension (mm)			Dynamic load (N)
	bore	O.D.	width	
22308EX-V	40	90	33	185,000
22309EX-V	45	100	36	230,000
22310EX-V	50	110	40	280,000
22311EX-V	55	120	43	325,000
22312EX-V	60	130	46	390,000
22313EX-V	65	140	48	415,000
22314EX-V	70	150	51	480,000
22315EX-V	75	160	55	550,000
22316EX-V	80	170	58	595,000
22317EX-V	85	180	60	665,000
22318EX-V	90	190	64	745,000
22319EX-V	95	200	67	815,000
22320EX-V	100	215	73	975,000
22322EX-V	110	240	80	1,150,000
22324EX-V	120	260	86	1,250,000
22326EX-V	130	280	93	1,450,000

- Tolerances: O.D. - P6 equivalent; Bore - P5 equivalent.
- Increased radial clearance for vibrating application.
- "W33" suffix - with oil hole & groove on O.D..

NACHI

NACHI-FUJIKOSHI CORP.

<http://www.nachi.com/>

Shiodome Sumitomo Bldg. 17F, 1-9-2 Higashi-Shinbashi, Minato-ku, Tokyo 105-0021, Japan

International Tel:+81-3-5568-5240 Fax:+81-3-5568-5236
 Japanese Tel:+81-3-5568-5111 Fax:+81-3-5568-5206



CATALOG NO. B1034E

2009.11.Q-EDI-MIZUNO